



General Product Description

Protecta® FR Board is designed to prevent the spread of fire and smoke through openings in fire rated walls and floors where openings are formed to allow the installation of multiple building services. Protecta® FR Board will also maintain the acoustic design performance in fire rated walls and floors.

Protecta® FR Board consists of a high density stone wool core, over-coated with Protecta® FR Coating. The top coating provides additional protection by significantly reducing the permeability of the stone wool core and prevents the passage of hot gases, thus reducing the temperature rise on the unexposed side and reducing heat conduction through the building services. Protecta® FR Board is available with top coating on one or two sides, selected on the basis of installation considerations and fire resistance.

On site, Protecta® FR Board must be used together with Protecta® FR Acrylic for sealing around building services and the surrounding construction.

Properties & Precautions

- Classified for all types of constructions with or without building service penetrations
- Simple and very quick to install
- Easy to retrofit additional building services after installation
- Permanently flexible - will accommodate movements during fire and smaller movements in the construction it has been fitted within
- Suitable for most surfaces, including concrete, bricks, Leca, steel, wood, gypsum, glass, PVC and most non-porous surfaces
- May be used in unlimited lengths in walls with heights up to 1200 mm. In floors the maximum opening dimension is 1200 x 2400 mm
- May be installed in gypsum walls without framing around the opening
- Halogen free with added fungicides
- Once fully cured, the coated board resists water and frost
- Protecta® FR Board can be supplied with a smooth surface
- The fire performance specification of the board has been derived when the seal has been let to cure for a month
- Precautions are required to be taken to prevent a person stepping onto a blank horizontal penetration seal
- Please read the Installation Instructions before usage

Resistance to Fire

Construction	Description	Classification
Flexible walls comprise gypsum, masonry, aerated concrete or concrete	Up to 2400 mm wide by 1200 mm high blank seal with double 50mm Protecta FR Board 1-S	EI 120 (E 120)
Rigid walls comprise masonry, aerated concrete or concrete	Up to 2400 mm wide by 1200 mm high blank seal with single 60mm Protecta FR Board 2-S	EI 90 (E 240)
	Up to 2400 mm wide by 1200 mm high blank seal with double 60mm Protecta FR Board 2-S	EI 180 (E 240)
Rigid floors comprise aerated concrete or concrete	Up to 2400 mm by 1200 mm blank seal with single 60mm Protecta FR Board 2-S	EI 90 (E 120)

NB. Please see the product's Installation Instructions for full details!



Sound Insulation

Description	Sound reduction
Single 50mm Protecta FR Board 2-S	55 dB
All other configurations	> 55 dB

Protecta® FR Board has been tested at BM Trada (UKAS accredited); according to EN ISO 10140-2:2010.

Emission Data (indoor air quality)

Compound	Emission rate after 4 weeks
TVOC	0.20 mg/m ³ h
Formaldehyde	n.d.
Ammonia	n.d.
Carcinogenic	n.d.
n.d. means not detected	

Protecta® FR Board complies with the requirements of BREEAM according to the M1 Protocol for Chemical and Sensory Testing of Building Materials as published by RTS version 15.12.2004 which is the best possible environmental and indoor hygiene health protection mark for coatings. Tested by Eurofins Product Testing, report number 392-2014-00000407B.

Technical Data

Condition	Ready for use, pre-coated boards
Density	Board: 160 – 180 kg/m ³ Coating: 1.3 – 1.4 kg/ltr
Flash point	None
Non-sticky	Max. 75 minutes (sealant)
Film forming	Max. 25 minutes (sealant)
Totally hardened	3 to 5 days depending on thickness and temperature
Flexibility	Low to medium, 12.5%
Thermal conduct.	0.038 W/mK
Storage	May be stored for a long period of time. To be stored in temperatures between 5°C and 30°C
Compatibility	Suitable for use with most materials, but should not be used in direct contact with bituminous materials
Limitations	If the boards are to be used in permanently humid areas Protecta® FR Coating should be applied over the sealant
Temperature range	-30°C to +80°C (when hardened)
Installation temp.	+5°C to +50°C
Colour	White surface, green core FR Acrylic: NCS 1202 – Y26R, RAL 9002
Packaging	FR Board 1-S 50x600x1200 mm: 80 pcs per pallet FR Board 2-S 60x600x1200mm: 72 pcs per pallet